



Densiphalt® · Densitop®

– all Densit® products have an extremely dense structure with very low water content



High durability

Densiphalt® and Densitop® withstand tough daily wear from heavy vehicles, aircrafts, forklift trucks, etc.



Joint-free

Densiphalt® is joint-free which increases speed of installation, reduces costs and requires only minimum maintenance.



Dust-free surface

The dense surface of Densiphalt® and Densitop® makes them dust free and therefore ideal for indoor areas in warehouses, production facilities and offices, etc.



Early trafficking

Densiphalt® and Densitop® can usually be used after only 24 hours' hardening time at 20 °C. This ensures minimum downtime for the customer's operations and activities.




Withstands high loads

Densitop® and Densiphalt® withstand very high static loads from racking systems, forklift trucks, heavy vehicles, containers and aircrafts. Furthermore, they are very resistant to rutting.




Resistant to freeze-thaw

Densiphalt® and Densitop® are both documented and classified as "very freeze-/thaw-resistant", which means they can withstand repeated temperature fluctuations.



Easy to clean

Densitop® and Densiphalt® floorings are easy to clean because of their dense and high strength surfaces. Densitop® withstands effective cleaning with hot water and steam cleaning under pressure.



Maintenance-free

Densiphalt® and Densitop® are extremely tough floorings that last for many years with no maintenance. A small degree of maintenance should, however, be expected for outdoor surfaces and in the food industry.



Swift installation

Densiphalt® and Densitop® are applied swiftly and efficiently on both smaller and large areas.



Impermeable

The extreme dense surface of Densiphalt® and Densitop® make them liquid-resistant, chloride-resistant and resistant to many chemicals.